

TP30-E

Automatic Electrical hydraulic pump unit

Oil filter cartridge

25µ Filter capacity
Replaceable cartridge



Electric motor TEFC

5.5Kw - 230/400V
3Ph - 50/60Hz
4 poles (1500 rpm)
B5 - IP 55

Hydraulic pump

variable capacity:
8÷40 Lt/min
2÷11 US gpm



Pilot lights of the state of the hydraulic gun, manual, automatic and Jaws release pilot light

Extraction pilot lamp indicator

Pressure gauges 350 bar (5075 psi)
oil discharge and return line

Return pilot lamp indicator

Work selector / jaws release

Hand bar

Oil level indicator

The TP30-E is controlled directly by the operator with substantial increase in productivity

Model	Max. pressure		Oil flow rate		Power supply	Remote control power supply	Dimensions			Weight				IP			
	bar	psi	Lt/min	US gpm			Vdc	Width	Depth	Highth	with oil		without oil				
TP30-E	350	5075	8÷40	2÷11	5.5Kw-230/400V-50/60Hz-3Ph	24	700	27.6"	950	37.4"	1080	42.5"	360	794	270	596	30

TP30-PS

Automatic Pneumactical hydraulic pump unit

Oil filter cartridge

25µ Filter capacity
Replaceable cartridge



Pneumatic motor

4Kw
7 bar (100 psi)
4800 Lt/min (170 Cfm)

Hydraulic pump

variable capacity:
8÷40 Lt/min
2÷11 US gpm



Internal tool box for hydraulic gun

Pressure gauges 350 bar (5075 psi)
oil discharge and return line

Air supply pressure gauge

Internal tool box for working accessories, hydraulic hoses, electric cables c/w lockable door

Hand bar

Oil level indicator

The TP30-PS is controlled directly by the operator with substantial increase in productivity

Model	Max. pressure		Oil flow rate		Power supply	Air pressure required		Dimensions			Weight						
	bar	psi	Lt/min	US gpm		bar	psi	Width	Depth	Highth	with oil		without oil				
TP30-PS	350	5075	8÷40	2÷11	4Kw - 7 bar (100psi)-4800 Lt/min (170Cfm)	7	100	770	30.3"	920	36.2"	1000	39.4"	220	485	130	287